

PATENT ABSTRACTS OF JAPAN

(11) Publication number:

2003248251 A

(43) Date of publication of application: 05.09.2003

(51) Int. CI

G02F 1/35

H01S 3/30.

H04B 10/02.

H04B 10/18

(21) Application number:

(22) Date of filing:

2002048392 25.02.2002

(71) Applicant: NATIONAL INSTITUTE OF

ADVANCED INDUSTRIAL &

TECHNOLOGY

ALNAIR LABS:KK

SAKAKIBARA YOICHI (72) Inventor:

> **TOKUMOTO MADOKA ACHINAMI HIROTSUGU** KATAURA HIROMICHI

TANAKA YUICHI

MARK KENNETH ZHABORONSKI


(54) NOISE REDUCTION DEVICE FOR SIGNAL LIGHT AND METHOD FOR REDUCING NOISE **OF SIGNAL LIGHT**

(57) Abstract:

PROBLEM TO BE SOLVED: To contrive to prolong the span of a transmission distance by reducing amplified spontaneous emission (ASE) undesirably generated in optical communication.

SOLUTION: The noise reduction device uses a carbon nanotube as a saturable absorber 15. The saturable absorber ensures the functioning of blocking or reducing the transmission of the undesirable amplified spontaneous emission (ASE) or the like having low signal light intensity and of transmitting signal light having high optical intensity. The noise reduction device is inserted in a passage for the signal light in a bidirectional excitation type EDFA (erbium doped fiber amplifier) 50, for example, more particularly, the noise reduction device is inserted in the downstream part of the EDF 40 to contrive its use in the optical communication field of the carbon nanotube having a saturable absorption function.

COPYRIGHT: (C)2003,JPO



50:双方向励起型EDFA

この実施の形態の双方向助起型EDFAの領路構成図


















JAPANESE PATENT OFFICE

PATENT ABSTRACTS OF JAPAN

(11) Publication number: 20032482!

(43) Date of publication of application: 05.09.2

(51) Int. Cl

G02F 1/35

H01S 3/30、 H04B 10/02、 H04B 10/18

(21) Application number:

2002048392

(22) Date of filing:

25.02.2002

(71) Applicant: NATIONAL INSTITUTE OF

ADVANCED INDUSTRIAL &

TECHNOLOGY ALNAIR LABS:KK

(72) Inventor: S

SAKAKIBARA YOICHI

TOKUMOTO MADOKA ACHINAMI HIROTSUGU KATAURA HIROMICHI

TANAKA YUICHI

MARK KENNETH ZHABORO

(54) NOISE REDUCTION DEVICE FOR SIGNAL LIGHT AND METHOD FOR REDUCING NOISE OF SIGNAL LIGHT


(57) Abstract:

PROBLEM TO BE SOLVED: To contrive to prolong the span of a transmission distance by reducing amplified spontaneous emission (ASE) undesirably generated in optical communication.

SOLUTION: The noise reduction device uses a carbon nanotube as a saturable absorber 15. The saturable absorber ensures the functioning of blocking or reducing the transmission of the undesirable amplified spontaneous emission (ASE) or the like having low signal light intensity and of transmitting signal light having high optical intensity. The noise reduction device is inserted in a passage for the signal light in a bidirectional excitation type EDFA (erbium doped fiber

amplifier) 50, for example, more particularly, the reduction device is inserted in the downstream the EDF 40 to contrive its use in the optical concation field of the carbon nanotube having a salabsorption function.

COPYRIGHT: (C)2003, JPO



NO TO PARTIE WHEA

この実施の原因の具定性歴史が認め、の情報情報門

















RESEARCH

PRODUCTS

INSIDE DELPHION

Leg Out Work Files Seved Searches My Account

Search: Quick/Number Boolean Advanced Der

The Delphion Integrated View

Tools: Add to Work File: Create new Work I Get Now: PDF | More choices... View: INPADOC | Jump to: Top Go to: Derwent

> PTitle: JP2003248251A2: NOISE REDUCTION DEVICE FOR SIGNAL LIGHT.

> > METHOD FOR REDUCING NOISE OF SIGNAL LIGHT

Signal light noise reduction apparatus for optical communication, has Propert Title:

carbon nanotube serving as saturable absorber, inserted in path of signal

light of erbium doped fiber amplifier [Derwent Record]

JP Japan **PCountry:**

> A2 Document Laid open to Public inspection i

SAKAKIBARA YOICHI:

> **TOKUMOTO MADOKA**; ACHINAMI HIROTSUGU; KATAURA HIROMICHI;

TANAKA YUICHI;

MARK KENNETH ZHABORONSKI:

NATIONAL INSTITUTE OF ADVANCED INDUSTRIAL & TECHNOLOGY **P**Assignee:

ALNAIR LABS:KK

JP2002000048392

News, Profiles, Stocks and More about this company

2003-09-05 / 2002-02-25 Published / Filed:

Number:

G02F 1/35; H01S 3/30; H04B 10/02; H04B 10/18;

PECLA Code: G02F1/35D;

2002-02-25 JP2002000048392 **Priority Number:**

> **PAbstract:** PROBLEM TO BE SOLVED: To contrive to prolong the span of a

transmission distance by reducing amplified spontaneous emission

(ASE) undesirably generated in optical communication.

SOLUTION: The noise reduction device uses a carbon nanotube as a saturable absorber 15. The saturable absorber ensures the functioning of blocking or reducing the transmission of the undesirable amplified spontaneous emission (ASE) or the like having low signal light intensity and of transmitting signal light having high optical intensity. The noise reduction device is inserted in a passage for the signal light in a bi-directional excitation type EDFA (erbium doped fiber amplifier) 50, for example, more particularly, the noise reduction device is inserted in the

downstream part of the EDF 40 to contrive its use in the optical communication field of the carbon nanotube having a saturable

absorption function.

COPYRIGHT: (C)2003, JPO


VINPADOC



NOISE REDUCTION DEVICE FOR SIGNAL LIGHT AND METHOD FOR REDUCIN... Page 2 of 2









Family:

Show 4 known family members

8 Other Abstract

DERABS C2003-689836











this for the Gallery...



Copyright © 1997-2005 The Thoi

Subscriptions | Web Seminars | Privacy | Terms & Conditions | Site Map | Contact U